



**GULF WESTERN OIL**

**GO THE DISTANCE**



**PRODUCT CATALOGUE**

# COMPANY PROFILE

Gulf Western Oil is Australia's largest family owned manufacturer of lubricants and 2023 marks its 35<sup>th</sup> year of operation. With two million litres of base oil and blended oil storage capacity and four 30,000 litre blending tanks, Gulf Western's self-contained facility in Sydney's West was designed in consultation with, and successfully licensed by the New South Wales Environmental Protection Authority (EPA). Gulf Western Oil is dedicated to ensure that manufacturing at our facility functions at a high standard that takes into consideration the environment, their staff, the local community, their neighbours and the local wildlife.

Gulf Western Oil has the capacity to manufacture 60,000,000 litres per annum in a single shift and this is made possible by the use of state of the art equipment and the support of a highly experienced team who work amongst the technical, management and production areas of the business. Currently distributing throughout all states and territories of Australia, along with New Zealand, Fiji, New Caledonia, Tahiti, Vietnam, Tonga, Samoa, Kiribati, Christmas islands PNG and the Pacific Rim with our distribution network constantly growing.




• Gulf Western Oil Blending Facility in NSW

# MISSION STATEMENT

We are a market-focused organisation that develops and delivers innovative solutions to our customers needs, consistently working to outperform our opposition, deliver outstanding customer service and provide a dynamic and challenging workplace environment for our employees.














## DOWNLOAD OUR FREE NETLUBE APP FROM ITUNES

For further information on our range of products, simply download our free app from iTunes and Google Play, visit our website - [www.gulfwestern.com.au](http://www.gulfwestern.com.au) or call our free hotline number - 1800 248 919 between 8am-5pm Monday-Friday.



\*Disclaimer: Icons are shown throughout this catalogue for illustrative/display purposes to assist customers with identifying what products best suit their applications. Please note: Many Gulf Western products can be used for various purposes and amongst different applications, so if you are unsure, please contact us on our free hotline 1800 248 919 for technical advice.

# CONTENTS

<b>HEAVY DUTY DIESEL</b>		<b>4</b>
<b>PASSENGER CARS</b>		<b>14</b>
<b>TWO STROKE, FOUR STROKE &amp; MARINE</b>		<b>27</b>
<b>HYDRAULIC OILS</b>		<b>29</b>
<b>COMPRESSOR OILS</b>		<b>35</b>
<b>GEAR OILS</b>		<b>37</b>
<b>TRANSMISSION FLUIDS</b>		<b>43</b>
<b>INDUSTRIAL</b>		<b>51</b>
<b>GREASES</b>		<b>56</b>
<b>COOLANTS</b>		<b>61</b>
<b>AEROSOLS</b>		<b>63</b>
<b>WORKSHOP MAINTENANCE</b>		<b>64</b>
<b>SPECIALISED PRODUCTS</b>		<b>69</b>

# ABBREVIATIONS

**ACEA** - Association des Constructeurs Europeens d'Automobiles  
**OEM** - Original Equipment Manufacturer  
**API** - American Petroleum Institute  
**NMMA** - National Marine Manufacturers Association  
**ILSAC** - International Lubricant Standardization and Approval Committee  
**SAPS** - Sulphate Ash, Phosphorous Sulphur  
**SAE** - Society of Automotive Engineers  
**ISO** - International Standards Organization  
**HVI** - High Viscosity Index  
**LPG** - Liquid Petroleum Gas  
**HDDO** - Heavy Duty Diesel Oil  
**SHPD** - Super High Performance Diesel  
**STOU** - Super Tractor Oil Universal  
**JASO** - Japanese Automotive Standards Organization

**EP** - Extreme Pressure  
**CVT** - Continuously Variable Transmission  
**DPF** - Diesel Particulate Filter  
**SCR** - Selective Catalyst Reduction  
**UTTF** - Universal Tractor Transmission Fluid  
**TC-W3** - Two Cycle Water-Cooled  
**FC-W** - Four-Stroke Cycle Water-Cooled  
**VPI** - Vapour Phase Inhibitor  
**PAO** - Polyalphaolefin  
**EPA** - Environmental Protection Authority  
**NLGI** - National Lubricating Grease Institute  
**OAT** - Organic Acid (Additive) Technology  
**VG** - Viscosity Grade

# HEAVY DUTY DIESEL

## TOP DOG® INDESTRUCTIBLE 15W-40 SYNTHETIC



### SPECIFICATIONS

API CK-4, CJ-4, CI-4 Plus, CI-4, Cummins CES20086, 20081, Detroit Diesel DFS 93K222, 93K218, Mack EOS 4.5, EO-O Premium Plus, Volvo VDS 4.5, VDS 4, ACEA E9, E7, MB 228.31, MAN 3575, Deutz DQC III-10 LA, Ford WSS-M2C171-F1, JASO DH-2.

### DESCRIPTION

**TOP DOG® INDESTRUCTIBLE 15W-40** is an uncompromising, next generation Heavy Duty Diesel Engine Oil containing Indestructible Additive Technology specifically designed to protect high powered, turbo charged Heavy Duty Diesel Engines.

### SUMMARY OF BENEFITS

- Formulation contains performance enhancing and superior wear protection technology that far exceeds the requirements of the new API CK-4 lubricant specification and previous specifications including API CJ-4.
- Fully backwards compatible with all current high HTHS Heavy Duty Diesel Engine Classification and meets the majority of modern engine manufacturer's specifications.
- Developed to meet the low ash requirements of today's heavy duty diesel engines to ensure compatibility with exhaust after-treatment systems including DPFs and AdBlue.
- Designed to significantly exceed the requirements of API CK-4, which is the latest Heavy Duty Diesel Engine Oil classification released in December 2016 by the American Petroleum Institute with significant improvement in wear protection.
- Wear metals for key engine components in extended service field trials and API approval testing show an average wear reduction of 52% compared to some commercially available CK-4 engine oils.
- API licensed and listed against Cummins CES 20086 meaning that it can be used in Cummins engine whilst maintaining full warranty protection for engines protected by the Cummins' Warranty Plus extended engine warranty protection plan.

PRODUCT CODE	PACK SIZE
300021B	IBC (1000L)
300021	205L
320021	20L

# HEAVY DUTY DIESEL

## TOP DOG® CK-4 15W-40 MINERAL



### SPECIFICATIONS

API CK-4, CJ-4, CI-4 Plus, API SN, ACEA E9, Caterpillar ECF-3, Cummins 20086, Mack EOS 4.5, Mercedes-Benz sheet 228.31, Volvo VDS 4.5, MTU Type 2.1, JASO DH-2.

### DESCRIPTION

**TOP DOG® CK-4 SAE 15W-40** is a premium, high performance, mineral oil based heavy duty diesel engine oils meeting the latest API CK-4 Heavy Duty Diesel performance specification making it suitable for use in the latest engines produced by major OEMs including Cummins, Caterpillar, Detroit Diesel and Volvo/Mack.

### SUMMARY OF BENEFITS

- Backwards compatible with other API Heavy Duty Diesel performance categories such as CJ-4, CI-4 Plus, CI-4 and CH-4.
- Provides protection for exhaust after-treatment systems including Diesel Particulate Filters (DPF) as well engines using AdBlue (SCR) technologies.
- Excellent mixed fleet oil as meets European ACEA E9 as well as JASO DH-2 performance levels
- Passing all the engine performance parameters of API SN, TOP DOG CK-4 SAE 15W-40 can also be used in petrol powered vehicles.
- Enhanced viscosity retention through use of highly shear stable viscosity modifiers.
- Greatly reduced engine wear giving extended engine life.
- Reduced oil consumption.

PRODUCT CODE	PACK SIZE
300058B	IBC (1000L)
300058	205L
320058	20L

# HEAVY DUTY DIESEL

## TOP DOG GLOBAL® MINERAL 15W-40 LOW SAPS



### SPECIFICATIONS

CJ4/CI4+/CI4/CH4/SN, ACEA E9/E7, Cummins 20081, Mack EO-N Premium Plus, Detroit Diesel DDC 93K218, CAT ECF3, 2, 1-a, MB 228.31, MAN 3575, MAN 3275, MTU Type 2.1, Volvo VDS-4, VDS-3, Renault RLD-3, Deutz QDC III-05, JASO DH-2, Allison C4.

### DESCRIPTION

**TOP DOG GLOBAL® MINERAL 15W-40** is a premium, OEM approved, heavy duty high performance diesel engine oil meeting the latest in API additive technology and US HDDO EOM requirements from Mack, Volvo, Cummins, Detroit Diesel and Caterpillar.

### SUMMARY OF BENEFITS

- Low SAPS formulation makes it suitable for use in engines fitted with Diesel Particulate Filters.
- Ideal for extended drain intervals and is an excellent multi fleet oil.
- Recommended for US, European and Japanese four stroke heavy duty diesel engines including the latest generation of highly tuned emission controlled engines including those with exhaust gas recirculation systems, SCR treatment systems and Diesel Particulate Filters.
- Suitable where extended drain intervals are required (supported by routine oil analysis) and for equipment operating under the most extreme conditions.
- Also suitable for stationary engines, petrol engines and 4WD's making it an ideal mixed fleet oil.
- Suitable for use as a hydraulic oil where a 10W-40 or 15W-40 is called for and as a transmission oil where the Allison C3/C4 specification is required.
- Suitable for use in vehicles meeting the most recent exhaust emission standards including US EPA 2010 TIER 4, Euro V and Australian ADR 80/01 standards.

PRODUCT CODE	PACK SIZE
30018B	IBC (1000L)
30018	205L
32018	20L
30518	5L

# HEAVY DUTY DIESEL

## TOP DOG GLOBAL® PLUS 10W-40 SYNTHETIC



### SPECIFICATIONS

CJ4/C14+/C14/CH4/SN, ACEA E9/E7, Cummins 20081, Mack EO-N Premium Plus, Detroit Diesel DDC 93K218, CAT ECF3, 2, 1-a, MB 228.31, MAN 3575, MAN 3275, MTU Type 2.1, Volvo VDS-4, VDS-3, Renault RLD-3, Deutz QDC III-05, JASO DH-2, Allison C4.

### DESCRIPTION

**TOP DOG GLOBAL® PLUS 10W-40** Synthetic is a premium, OEM approved, heavy duty high performance diesel engine oil meeting the latest in API additive technology and US HDDO OEM requirements from Mack, Volvo, Cummins, Detroit Diesel and Caterpillar.

### SUMMARY OF BENEFITS

- Low SAPS formulation making it suitable for use in engines fitted with Diesel Particulate Filters.
- Ideal for extended drain intervals and is an excellent multi fleet oil.
- Recommended for US, European and Japanese four stroke heavy duty diesel engines including the latest generation of highly tuned emission controlled engines including those with exhaust gas recirculation systems, SCR treatment systems and Diesel Particulate Filters.
- Suitable where extended drain intervals are required (supported by routine oil analysis) and for equipment operating under the most extreme conditions.
- Also suitable for stationary engines, petrol engines and 4WD's making it an ideal mixed fleet oil.
- Suitable for use as a hydraulic oil where a 10W-40 or 15W-40 is called for and as a transmission oil where the Allison C3/C4 specification is required.
- Suitable for use in vehicles meeting the most recent exhaust emission standards including US EPA 2010 TIER 4, Euro V and Australian ADR 80/01 standards.

PRODUCT CODE	PACK SIZE
30013B	IBC (1000L)
30013	205L
32013	20L
30513	5L

# HEAVY DUTY DIESEL

## TOP DOG® XDO 15W-40 MINERAL



\*NOT RECOMMENDED FOR ENGINES FITTED WITH DIESEL PARTICULATE FILTERS.

### SPECIFICATIONS

API CI-4/SL, ACEA E7, Volvo VDS-3, MACK EO-N, Cummins CES 20078/77/76, Caterpillar ECF-2, ZF TE-ML-02C/03A+04B/04C/07C, MAN 3275, Mercedes Benz 228.3, Type 2, Allison C4, RVI RLD-2, Global DHD-1, Deutz DRC 111-10, Detroit Diesel DDC 93K215.

### DESCRIPTION

**TOP DOG® XDO 15W-40** is a heavy duty high performance, OEM approved diesel engine oil meeting the latest in lubrication technology formulated for Australia's harsh environment meeting OEM requirements from Mack, Volvo, Detroit and Cummins.

### SUMMARY OF BENEFITS

- Provides superior protection against engine wear and sludge build up ensuring a cleaner engine.
- Offers extended drain intervals, reduced oil consumption and excellent low temperature viscometrics for reduced wear on start up.
- Recommended for US, European and Japanese four stroke heavy duty diesel engines including the latest generation of highly tuned emission controlled engines including those with exhaust gas recirculation systems and SCR treatment systems.
- Suitable where extended drain intervals are required (supported by routine oil analysis) and for equipment operating under the most extreme conditions.
- Suitable for stationary engines, petrol engines and 4WD's making it an ideal mixed fleet oil.
- API licensed and listed against Cummins CES 20078 meaning that it can be used in Cummins engine whilst maintaining full warranty protection for engines protected by the Cummins' Warranty Plus extended engine warranty protection plan.
- Suitable for use as a hydraulic oil where a 15W-40 is called for and as a transmission oil where the Allison C3/C4 specification is required.

PRODUCT CODE	PACK SIZE
30012B	IBC (1000L)
30012	205L
32012	20L
31012	10L
30612	6L
30512	5L
30112	1L



# HEAVY DUTY DIESEL

## SYNFLEET MX 10W-40 FULL SYNTHETIC LOW SAPS



### SPECIFICATIONS

CJ4/CI4+/CI4/CH4/SN, ACEA E9, Cummins 20081, Mack EO-N Premium Plus, Detroit Diesel DDC 93K218, CAT ECF3, 2, 1-a, MB 228.31, MAN 3575, MAN 3275, MTU Type 2.1, Volvo VDS-4, VDS-3, Renault RLD-3, Deutz DQC III-05, JASO DH-2, Allison C4.

### DESCRIPTION

**SYNFLEET MX 10W-40** Full Synthetic is an ultra-premium, OEM approved, heavy duty high performance diesel engine oil meeting the latest in API additive technology and US HDDO OEM requirements from Mack, Volvo, Cummins, Detroit Diesel and Caterpillar.

### SUMMARY OF BENEFITS

- Low SAPS formulation making it suitable for use in engines fitted with Diesel Particulate Filters and is ideal for extended drain intervals and is an excellent multi fleet oil.
- Recommended for US, European and Japanese four stroke heavy duty diesel engines including the latest generation of highly tuned emission controlled engines including those with exhaust gas recirculation systems, SCR treatment systems and Diesel Particulate Filters.
- Suitable where extended drain intervals are required (supported by routine oil analysis) and for equipment operating under the most extreme conditions.
- Also suitable for stationary engines, petrol engines and 4WD's making it an ideal mixed fleet oil.
- Suitable for use as a hydraulic oil where a 10W-40 or 15W-40 is called for and as a transmission oil where the Allison C3/C4 specification is required.
- Can be used in vehicles meeting the most recent exhaust emission standards including US EPA 2010 TIER 4, Euro V and Australian ADR 80/01 standards.

PRODUCT CODE	PACK SIZE
30014B	IBC (1000L)
30014	205L
32014	20L

# HEAVY DUTY DIESEL

## EURO SYN 10W-40 FULL SYNTHETIC LOW SAPS



### SPECIFICATIONS

ACEA E6/E9/E7/E4, API CK-4, JASO DH-2, CAT ECF-3, Cummins CES 20086, Detroit Diesel DDC93K222, Deutz DQC IV-10-LA, Mack EOS-4.5 MAN M 3477, M 3271-1, MB 228.51, MTU Type 3.1, Renault Truck RLD-4, Scania Low Ash, Volvo VDS-4.5.

### DESCRIPTION

**EURO-SYN 10W-40** is a fully synthetic, extra high performance low ash European engine oil formulated for the most severe performance, low emission European engines fitted with 'after treatment systems' including centrifuges, Diesel Particulate Filters and additional filtration.

### SUMMARY OF BENEFITS

- A fully synthetic formulation that can extend drain intervals up to 100,000kms (supported by routine oil analysis within OEM guidelines).
- Is suitable for use with NOx reduction systems and particulate filters and is designed for use in combination with low sulfur diesel fuel (maximum 50ppm).
- Recommended for low emission engines. It is suggested for DAF, Deutz, Iveco, MAN, Mercedes-Benz, Renault, Scania and Volvo Euro 4 or Euro 5 engines calling for the above specifications and other European engines calling for SHPD (Super High Performance Diesel) rated engine oil such as EURO 1 - EURO VI.
- Also suitable for Japanese and American diesel engines and mixed fleets calling for a CK-4 or JASO DH-2 rated oil.

PRODUCT CODE	PACK SIZE
30009B	IBC (1000L)
30009	205L
32009	20L

# HEAVY DUTY DIESEL

## EURO SYN LV 5W-30 FULL SYNTHETIC



### SPECIFICATIONS

ACEA E6/E4/E9/E7, MB 228.51 (formulation approved by Daimler Benz), Scania LDF-4, MAN M 3677/3575/3477, MTU Type 3.1, Deutz DQC-IV-10 LA.


### DESCRIPTION

**EURO SYN LV 5W-30** is an advanced, full synthetic low viscosity ultra high performance diesel (UHPD) engine oil offering exceptional engine protection while also offering fuel economy benefits.

### SUMMARY OF BENEFITS

- Low ash for complete DPF protection.
- Allowable drain in excess of 100,000km whilst maintaining complete protection.

PRODUCT CODE	PACK SIZE
320055	20L



## TURBO DIESEL LA 15W-40 MINERAL

### SPECIFICATIONS

API CG-4/SJ, MB 228.3, MAN 3275, Deutz DQC-II, MTU 2.0, Mack EO-M, Cummins 20077, Caterpillar ECF-1a, TO-2.

### DESCRIPTION

**TURBO DIESEL LA 15W-40** is a heavy duty diesel engine oil suitable for use in pre-2000 diesel and petrol engines or modern engines calling for API CG4/SJ specifications.


### SUMMARY OF BENEFITS

- Formulated for Australia's harsh conditions hence will provide protection against engine wear, reduce oil consumption and offer good soot control to reduce oil thickening.
- Suitable for a wide range of heavy duty diesel engines, petrol engines, 4WD's, stationary engines and mobile hydraulic units calling for the specifications listed above.

PRODUCT CODE	PACK SIZE
30002	205L
32002	20L

# HEAVY DUTY DIESEL

## TURBOIL SAE 30 & SAE 40 MINERAL



### SPECIFICATIONS

CF4/CF2/CF/SG, Detroit Diesel 7SE2709505, Mil-I-2104D&E, Allison C4, Caterpillar TO-2 and MTU oil category 2.

### DESCRIPTION

The **TURBOIL** range is available in both SAE 30 and SAE 40 viscosities. It is a low detergent, mono grade engine oil that helps reduce oil consumption, protect against oil oxidation and maintains engine cleanliness.

### SUMMARY OF BENEFITS

- It is ideally suited for two stroke Detroit Diesel engines that must not use a multi grade engine oil, and with an ash content of less than 0.8%.
- Also suitable for pre-1991 earthmoving, agricultural and transport equipment calling for a mono grade oil in four stroke applications.

#### SAE 30 -

PRODUCT CODE	PACK SIZE
30004	205L
32004	20L

#### SAE 40 -

PRODUCT CODE	PACK SIZE
30005	205L
32005	20L

# HEAVY DUTY DIESEL

## MONOIL SAE 30 MINERAL



### SPECIFICATIONS

API SJ/CF, Caterpillar TO-2, Allison C3.

### DESCRIPTION

**MONOIL SAE 30** is suitable for diesel engines calling for an API CF grade or lower and is also suitable for petrol powered engines requiring an API SJ performance level or lower.

### SUMMARY OF BENEFITS

- Ideal for stationary petrol or diesel engines from manufacturers including Briggs and Stratton.
- Also meets the requirements for many older engines such as Leyland, International Harvester, Gardner, Fiat and Bedford.

PRODUCT CODE	PACK SIZE
30006	205L
32006	20L

## FARMOIL STOU 15W-40 MINERAL



### SPECIFICATIONS

API CG-4/SF, ACEA E3, JD 20C, CNH MAT 3525, 3526, Massey Ferguson M1143, M1145, API GL-4.

### DESCRIPTION

**FARMOIL STOU 15W-40** is a STOU (Super Tractor Oil Universal) formulated to meet all the requirements of most modern tractor manufacturers calling for a STOU type oil. It provides protection against brake chatter and squawk.

PRODUCT CODE	PACK SIZE
30008B	IBC (1000L)
30008	205L
32008	20L

# PASSENGER CARS

## SYN-X 3000® 10W-40 SYNTHETIC



### SPECIFICATIONS

API SN/CF, ACEA A3/B4, MB 229.3, VW 502.00/505.00.

### DESCRIPTION

**SYN-X 3000® 10W-40** is a high performance, high quality, synthetic premium grade passenger car/light diesel engine oil meeting the latest in API additive technology and fuel efficiency.

### SUMMARY OF BENEFITS

- Formulated with synthetic base stock ensuring cleaner engines, reduced engine wear and reduced oil oxidation.
- Offers rapid start up flow that reduces cold start wear and has excellent thermal stability.
- Recommended for most 4, 6 and 8 cylinder passenger cars manufactured from 1980 onward.
- Recommended for Petrol, LPG and lightly loaded diesel engines.
- It is suitable for turbo charged and super charged engines.

PRODUCT CODE	PACK SIZE
30037B	IBC (1000L)
30037	205L
32037	20L
30537	5L
30137	1L

# PASSENGER CARS

## SYN-X 4000 5W-30 FULL SYNTHETIC



\*NOT SUITABLE FOR MOTORCYCLES FITTED WITH WET CLUTCHES.

### SPECIFICATIONS

SP/ILSAC GF-6A, DX1G2, Ford WSS-M2C-961-A1, Chrysler MS6395.

### DESCRIPTION

**SYN-X 4000 5W-30** is a premium, full synthetic, high performance, passenger car motor oil. Suitable for use in advanced, high compression engines including turbo gasoline direct injection engines where it can prevent LSPI (low speed pre-ignition) and timing chain wear. Meets SAE 5W-30, API SP/ILSAC GF-6A, DX1G2, Ford WSS-M2C-961-A1, Chrysler MS-6395.

### SUMMARY OF BENEFITS

- Suitable for turbo charged and super charged engines.
- Recommended for Petrol, LPG and lightly loaded diesel engines.

PRODUCT CODE	PACK SIZE
60001	205L
62001	20L
60501	5L

## SYN-X 7000 5W-30 FULL SYNTHETIC



### SPECIFICATIONS

Ford WSS-M2C-913D (913C, 913B, 913A), ACEA A5/B5, API SL/CF, Renault 0700.

### DESCRIPTION

**SYN-X 7000 5W-30** is a energy conserving, fully synthetic engine oil specially engineered for late model Ford passenger cars. Formulated to meet Ford requirement WSS-M2C-913D and can also be used where 913C, 913B and 913A specs are called for. Can reduce consumption by up to 3%.

PRODUCT CODE	PACK SIZE
60020	205L
62020	20L
60520	5L

# PASSENGER CARS

## SYN-X 5000 5W-40 FULL SYNTHETIC



### SPECIFICATIONS

SP/CF, ACEA A3/B3/B4, MB-Approval 229.5, RN 700/710, VW 502/505, PSA B71-2300.

### DESCRIPTION

**SYN-X 5000 5W-40** is a full synthetic high performance engine oil providing ultimate protection for modern high performance engines.

### SUMMARY OF BENEFITS

- Advanced additive technology providing superior engine cleanliness and high temperature protection in high output turbo charged or naturally aspirated engines including diesel vehicles.
- Super oxidation stability compared to a mineral oil based lubricant.
- Outstanding low temperature viscometrics for reduced wear at start up.
- Excellent mixed fleet oil.
- Reduces fuel consumption due to superior technology.
- Suitable for a wide range of vehicle manufacturers from Europe, Japan and America.

PRODUCT CODE	PACK SIZE
60037	205L
62037	20L
60537	5L
60137	1L



# PASSENGER CARS

## SYN-X 6000 5W-40 FULL SYNTHETIC



### SPECIFICATIONS

API SP, ACEA C3, MB 229.51, VW 502, 505, 501, BMW Long Life 04, Porsche A40, GM DX2, PSA Peugeot Citroën B71-2296.

### DESCRIPTION

**SYN-X 6000 5W-40** is a premium grade, full synthetic ultra-high performance engine oil suitable for petrol, diesel and LPG applications. It meets the latest API SP and ACEA C3 specifications. Suitable to be used where the following specifications are called for: API SP/SN Plus/SN or earlier, ACEA C3, MB 229.51, VW 505/502/505.1, Porsche A40, BMW LL04, GM DX2, PSA Peugeot Citroën B71-2296. Mid saps level makes it suitable for vehicles fitted with particulate filters.

### SUMMARY OF BENEFITS


- Suitable for vehicles fitted with Diesel Particulate Filters.
- Recommended for cars calling for GM DX2 approved formulations, Japanese and American vehicles calling for API SP or earlier grades, super charged and turbo charged engines, lightly loaded diesel engines and LPG vehicles.

- Although it has not been formally tested, we are fully confident of the performance of SYN-X 6000 in applications calling for VW 504/VW 507 specifications.

PRODUCT CODE	PACK SIZE
30017B	IBC (1000L)
30017	205L
36017	60L
32017	20L
30517	5L
30117	1L

# PASSENGER CARS

## SYN-STAR LV 5W-20 FULL SYNTHETIC



### SPECIFICATIONS

API SP, ILSAC GF-6A, Chrysler MS-6395, Ford M2C-960-A1, DX1G2.

### DESCRIPTION

**SYN-STAR LV 5W-20** is a fully synthetic specially engineered low viscosity, high performance passenger car engine oil suitable for late model passenger motor vehicles including low emission engine vehicles and hybrid vehicles.

PRODUCT CODE	PACK SIZE
60028B	IBC (1000L)
60028	205L
62028	20L

## SYN-STAR 0W-30 FULL SYNTHETIC LOW SAPS



### SPECIFICATIONS

API SP, Low SAPS and ACEA C3, Ford M2C950-A.

### DESCRIPTION

**SYN-STAR 0W-30** is a fully synthetic specially engineered low viscosity, high performance passenger car engine oil suitable for late model diesel and petrol powered motor vehicles including those fitted with Diesel Particulate Filters.

PRODUCT CODE	PACK SIZE
60023B	IBC (1000L)
60023	205L
62023	20L
60523	5L

# PASSENGER CARS

## SYN-X LV 0W-20 FULL SYNTHETIC, LOW ASH



### SPECIFICATIONS

SAE 0W-20, ACEA C5, API SP, ILSAC GF-6A, BMW LL17FE+, Chrysler MS-12145, Ford WSS-M2C-960-A1, MB 229.71, Volvo VCC RBS0-2AE.

### DESCRIPTION

**SYN-X LV 0W-20** is a full synthetic ultra high performance engine oil suitable for a wide range of modern gasoline and diesel powered vehicles offering ultimate engine performance and protection whilst delivering enhanced fuel economy. Suitable for many European, US and Asian diesel and petrol engines including hybrids. Offers protection for diesel and gasoline particulate filters.

PRODUCT CODE	PACK SIZE
320204	20L
305204	5L

## ENERGY PLUS 5W-30 FULL SYNTHETIC LOW SAPS



### SPECIFICATIONS

VW 504/507 Approval, ACEA C3, MB 229.51, BMW LL-04.

### DESCRIPTION

**ENERGY PLUS 5W-30** is a specially engineered fully synthetic Low SAPS passenger car engine oil manufactured for VW's latest top tier engine specification for long drain intervals.

PRODUCT CODE	PACK SIZE
60013B	IBC (1000L)
60013	205L
62013	20L
60513	5L

# PASSENGER CARS

## EURO ENERGY 5W-30 FULL SYNTHETIC LOW SAPS



### SPECIFICATIONS

API SP, ACEA C2/C3, MB 229.51, VW 502, 505, 501, BMW Long Life 04, Porsche, GM DX2, PSA Peugeot Citroën B712290.

### DESCRIPTION

**EURO ENERGY 5W-30** is a mid saps particulate filter safe full synthetic motor oil formulated for late model passenger motor vehicles running on diesel, petrol and LPG fuels. It is ideally suited to vehicles calling for the ACEA C3 specification such as VW, BMW and other European vehicles. Euro Energy meets API SP/SN Plus/SN, ACEA C2/C3 and is recommended where MB 229.31, 229.51, 229.52, 226.5, VW 502/505, BMW II-04, Porsche A40, GM DX2 and Renault RN0700/RN0710 are called for.

### SUMMARY OF BENEFITS

- Offers superior engine cleanliness, increased horse power, reduced wear and the ability to increase drain intervals within manufacturer guidelines.
- Recommended for most modern European petrol or diesel powered vehicles calling for ACEA C3, modern diesel engines calling for a GM DX2 approved formulation (DX2 is suitable for both Petrol and Diesel powered GM engines), American and Asian petrol powered or hybrid vehicles calling for API SP or earlier API performance grades.
- Also suitable for super charged and turbo charged engines, lightly loaded diesel engines and engines running on LPG fuel.

- Although it has not been formally tested against VW 504/VW 507, we are fully confident of the performance of EURO ENERGY in applications calling for VW 504/VW 507 specifications.

PRODUCT CODE	PACK SIZE
60002B	IBC (1000L)
60002	205L
62002	20L
60502	5L
60102	1L

# PASSENGER CARS

## EURO FORCE 5W-30 FULL SYNTHETIC LOW SAPS



### SPECIFICATIONS

ACEA C4, Renault RN0720, Ford M2C934-B.

### DESCRIPTION

**EURO FORCE 5W-30** is a fully synthetic ultra Low SAPS Diesel passenger car engine oil. It is recommended for vehicles calling for a ACEA C4 rated oil. Ideal for extended drain intervals. Suitable where ACEA C1 oils are recommended.

PRODUCT CODE	PACK SIZE
60007B	IBC (1000L)
60007	205L
62007	20L
60507	5L

## GULF 1 10W-60 FULL SYNTHETIC



### SPECIFICATIONS

SP/CF, ACEA A3/B4.

### DESCRIPTION

**GULF 1 10W-60** is a fully synthetic highly advanced, ultra high performance engine oil formulated with poly alpha olefin synthetic base oil technology. It is formulated to provide superior engine performance, reduced wear, increase oil drain intervals and reduced oil consumption. Suitable for most modern and older engines calling for API SP/CF specification or earlier. It is suitable for turbo charged, super charged engines and four stroke motorcycles fitted with wet clutches. It is recommended for Petrol, LPG and diesel engines.

PRODUCT CODE	PACK SIZE
30034	205L
30534	5L

# PASSENGER CARS

## PREMIUM ENERGY® 10W-30 SYNTHETIC



### SPECIFICATIONS

API SP, ILSAC GF-6A, Ford WSS-M2C-945A/946A, Chrysler MS6395.

### DESCRIPTION

**PREMIUM ENERGY® 10W-30** is a synthetic low viscosity, energy conserving premium grade passenger car engine oil offering the latest in API additive technology and fuel efficiency standards.

### SUMMARY OF BENEFITS

- Provides superior engine protection and offers advanced protection against cold start wear, oxidation while providing excellent thermal stability.
- Suitable for use in modern engine vehicles where a 7.5W or 10W-30 engine oil is called for or when superior fuel efficiency is desired.
- It meets the demanding ILSAC GF-6A resource conserving specification and is suitable for turbo charged and super charged engines.
- Recommended for Petrol, LPG and lightly loaded diesel engines.

PRODUCT CODE	PACK SIZE
30032B	IBC (1000L)
30032	205L
32032	20L
30632	6L
30532	5L
30132	1L

# PASSENGER CARS

## PROTECTA ULTRA 15W-50 SYNTHETIC



### SPECIFICATIONS

SL/CF, ACEA A3/B3.

### DESCRIPTION

**PROTECTA ULTRA 15W-50** is a high performing, synthetic, higher viscosity engine oil formulated for older and modern high performance engines requiring API SL, ACEA A3/B3 or earlier specifications.

PRODUCT CODE	PACK SIZE
30033B	IBC (1000L)
30033	205L
32033	20L
30533	5L

# PASSENGER CARS

## HI TECH PREMIUM 20W-50 MINERAL



### SPECIFICATIONS

API SN/SM/CF.

### DESCRIPTION

**HI TECH PREMIUM 20W-50** is a premium grade engine oil. It provides superior engine protection, reduces oil consumption, excellent anti-oxidation capabilities and offers excellent thermal stability.

PRODUCT CODE	PACK SIZE
30027B	IBC (1000L)
30027	205L
32027	20L
30627	6L
30527	5L
30127	1L

## PREMIUM GOLD 15W-40 SYNTHETIC



### SPECIFICATIONS

API SN/SM/CF.

### DESCRIPTION

**PREMIUM GOLD 15W-40** is a mid viscosity range premium grade engine oil. It provides superior protection against cold start wear, reduces oil consumption, excellent anti-oxidation capabilities and offers excellent thermal stability.

PRODUCT CODE	PACK SIZE
30021B	IBC (1000L)
30021	205L
32021	20L
30621	6L
30521	5L
30121	1L



# PASSENGER CARS

## XMP ENGINE OIL 20W-50 MINERAL



### SPECIFICATIONS

SL/CF.

### DESCRIPTION

**XMP ENGINE OIL 20W-50** is a multi-grade engine oil formulated with shear stable additives for use in a wide range of passenger cars and lightly loaded diesel engines. Also suitable for use in turbo charged engines.

PRODUCT CODE	PACK SIZE
30422	4L

## COMP 50 PLUS 25W-70 MINERAL



### SPECIFICATIONS

SN/CF.

### DESCRIPTION

**COMP 50 PLUS 25W-70** is a high viscosity engine oil formulated for both high revving, hard working race engines and it is also formulated for older, worn engines with oil consumption or fuming problems. It is a proven performance oil in heavily worked engines including those using methanol and nitro methane fuels. Recommended for turbo and supercharged engines, petrol, LPG and diesel powered engines and also suitable for motorcycles fitted with wet clutches such as V twin engines.

PRODUCT CODE	PACK SIZE
30024B	IBC (1000L)
30024	205L
32024	20L
30524	5L

# PASSENGER CARS

## COMP-R 40 & 50 10W-40 & 25W-50



### SPECIFICATIONS

SN/CF.

### DESCRIPTION

The **COMP-R** range is made up of high performance engine oils developed to protect high output engines during on-road as well as track usage. Compatible with all road fuels as well as common racing fuels including Avgas, Nitro methane and methanol. Exceptional engine protection from enhanced levels of zinc and moly containing anti-wear additives.

A viscosity grade offering the same exceptional engine protection is available regardless of whether you drive a "fast four" or a top fuel dragster.

### SUMMARY OF BENEFITS

- Synthetic and Full Synthetic formulations available to offer enhanced viscosity control at operating temperature.
- Race oil suitable for daily drive application offering outstanding wear protection without the need of reduced oil drain intervals.
- Outstanding wear protection due to high levels of zinc and organic molybdenum additives.
- Highly shear stable viscosity modifiers in COMP-R 40 resists viscosity loss under load.
- COMP-R 50 has shear-less formulations to ensure no viscosity loss due to temporary or permanent polymer shearing in the highest horsepower applications such as Top Fuel, Door Slammer and Funny Cars.
- Unlike some race only oil, an appropriate level of detergency means that the COMP-R range can also be used in high performance road cars without the need to reduce oil drain intervals.

#### COMP-R 40 (10W-40) -

PRODUCT CODE	PACK SIZE
320017	20L

#### COMP-R 50 (25W-50) -

PRODUCT CODE	PACK SIZE
320011	20L

## TWO STROKE, FOUR STROKE & MARINE

# OUTBOARD TC-W3 TWO STROKE SYNTHETIC



### SPECIFICATIONS

NMMA TC-W3® Registration Number: RL-331679Y.

### DESCRIPTION

**OUTBOARD TC-W3** is an ash less, high performance synthetic two stroke engine oil designed for use in water cooled outboard engines including oil injected engines. OUTBOARD TC-W3 will minimise spark plug fouling and is a low smoke formulation. Suitable for everyday boating and for high performance outboard engines. Dyed blue for identification.

PRODUCT CODE	PACK SIZE
30082B	IBC (1000L)
30082	205L
32082	20L
30482	4L
30182	1L

## TWO STROKE, FOUR STROKE & MARINE



### LAWN MOWER OIL SAE 30 MINERAL



#### SPECIFICATIONS

SAE 30, API SJ/CF.

#### DESCRIPTION

**LAWN MOWER OIL SAE 30** is monograde oil designed for the engines of four stroke lawn mowers and stationary engines including Honda, Briggs and Stratton. Dyed red for identification.

PRODUCT CODE	PACK SIZE
30084B	IBC (1000L)
30084	205L
32084	20L
30184	1L

### AIR COOLED TWO STROKE SYNTHETIC



\*NOT SUITABLE FOR WATER COOLED ENGINES OR OUTBOARD ENGINES.

#### SPECIFICATIONS

API TC, TB, TA, JASO FC.


#### DESCRIPTION

**AIR COOLED TWO STROKE** is premium two stroke oil suitable for use in air cooled two stroke engines such as lawn mowers, brush cutters, chain saws and other air cooled two stroke applications. Dyed green for identification.

PRODUCT CODE	PACK SIZE
30083B	IBC (1000L)
30083	205L
32083	20L
30483	4L
30183	1L

# HYDRAULIC OILS

## SUPERDRAULIC® MINERAL ISO 15, 22, 32, 46, 68 & 100



### DESCRIPTION

The **SUPERDRAULIC®** range of anti-wear hydraulic fluid is available in ISO Viscosity Grades 15, 22, 32, 46, 68 and 100. It is formulated using advanced Zinc Dithiophosphate additive technology providing superior protection against pump wear, excellent filterability, good thermal stability, low fluid/water interaction, excellent air release, foaming and demulsibility properties and good protection against corrosion.

### SUMMARY OF BENEFITS

- Formulated with premium quality additive packages delivering a ultra-high quality fluid meeting the requirements of the following pump manufacturers/OEM's: Rexroth (Bosch), Denison, Vickers, David Brown, Hagglund, Danfoss, Commercial Hydraulics, Racine, Sunstrand, Oilgear, Linde, Cincinnati Milacron, US Steel, General Motors AGMA, US Military, Eaton & AFNOR.
- Suitable for most hydraulic applications including transport, injection moulding, presses, machinery, agriculture, mining, earthmoving, cranes, industrial and most general hydraulic applications.
- Product is passed through an ultra-fine filtration process, this combined with only new virgin packaging offered by Gulf Western ensures excellent ISO Cleanliness levels.
- Offers good seal and paint compatibility.
- SUPERDRAULIC® meets many industry standards and OEM approvals that are not listed above, for a full listing please contact us.

### ISO 15 -

PRODUCT CODE	PACK SIZE
300092B	IBC (1000L)
300092	205L
320092	20L

### ISO 22 -

PRODUCT CODE	PACK SIZE
30078B	IBC (1000L)
30078	205L
32078	20L

# HYDRAULIC OILS

## SUPERDRAULIC® MINERAL ISO 15, 22, 32, 46, 68 & 100



CONTINUED..

### ISO 32 -

PRODUCT CODE	PACK SIZE
30061B	IBC (1000L)
30061	205L
32061	20L

### ISO 46 -

PRODUCT CODE	PACK SIZE
30062B	IBC (1000L)
30062	205L
32062	20L

### ISO 68 -

PRODUCT CODE	PACK SIZE
30063B	IBC (1000L)
30063	205L
32063	20L

### ISO 100 -

PRODUCT CODE	PACK SIZE
30064B	IBC (1000L)
30064	205L
32064	20L

# HYDRAULIC OILS

## SUPERDRAULIC® HVI HI TEMP ISO 32, 46, 68, 100



### DESCRIPTION

The **SUPERDRAULIC® HVI HI TEMP** range of high viscosity index, high temperature anti-wear hydraulic fluids is available in Viscosity Grades 32, 46, 68 and 100.

### SUMMARY OF BENEFITS

- Formulated using the same chemistry as the Superdraulic® range however is formulated with shear stable polymers making it suitable for use in applications where extra harsh conditions and heat are common.
- Offers excellent thermal stability and will suffer minimal viscosity loss over a wide range of temperatures.
- Dyed green for identification.

#### ISO 32 -

PRODUCT CODE	PACK SIZE
60061	205L
62061	20L

#### ISO 46 -

PRODUCT CODE	PACK SIZE
30081B	IBC (1000L)
30081	205L
32081	20L
30581	5L

#### ISO 68 -

PRODUCT CODE	PACK SIZE
30065B	IBC (1000L)
30065	205L
32065	20L
30565	5L

#### ISO 100 -

PRODUCT CODE	PACK SIZE
30091B	IBC (1000L)
30091	205L
32091	20L

# HYDRAULIC OILS

## GULF HARVESTER FLUID VG 46 & 68 MINERAL



### DESCRIPTION

**GULF HARVESTER HYDRAULIC FLUID** is an ultra high temperature, super shear stable hydraulic oil designed for use in extreme applications where very high temperatures are common, such as those experienced in Austoft and Cameco sugar cane harvesters.

### SUMMARY OF BENEFITS

- Formulated with extremely shear stable additives offering minimal viscosity loss, minimal oxidation and offers excellent thermal stability.
- Dyed green for identification.

#### ISO 46 -

PRODUCT CODE	PACK SIZE
30076B	IBC (1000L)
30076	205L

#### ISO 68 -

PRODUCT CODE	PACK SIZE
30072B	IBC (1000L)
30072	205L
32072	20L



# HYDRAULIC OILS

## SUPERDRAULIC® ZINC FREE HYDRAULIC 46 & 68 MINERAL



### DESCRIPTION

**ZINC FREE HYDRAULIC 46 & 68** are premium grade Zinc free formulations suitable for use in systems where silver plated bearings are common, such as Lucas PM – 500 series hydraulic pumps.

#### ISO 46 -


PRODUCT CODE	PACK SIZE
60006B	IBC (1000L)
60006	205L
62006	20L

#### ISO 68 -

PRODUCT CODE	PACK SIZE
30087B	IBC (1000L)
30087	205L

# HYDRAULIC OILS

## BIODRAULIC FR VG 46 & 68 FULL SYNTHETIC



### DESCRIPTION

**BIODRAULIC SYNTHETIC FR** is a biodegradable, fire resistant ester based synthetic hydraulic fluid available in viscosity grades ISO 46 & 68. It has independent Factory Mutual certification for fire resistance. It is more than 95% biodegradable making it ideal for use in equipment working in environmentally sensitive environments.

#### ISO 46 -

PRODUCT CODE	PACK SIZE
40002B	IBC (1000L)
40002	205L
42002	20L

#### ISO 68 -

PRODUCT CODE	PACK SIZE
40009B	IBC (1000L)
40009	205L
42009	20L

# COMPRESSOR OILS

## ULTRA CLEAR COMPRESSOR VG 46 & 68 FULL SYNTHETIC



\*NOT SUITABLE FOR USE IN COMPRESSORS PRODUCING AIR FOR BREATHING.

### SPECIFICATIONS

ISO/DP 6521 DAA, DAB, DAG, DAH; DIN 51506 VBL, VCL, VDL. Ashless, full synthetic compressor lubricants based upon PAO base oil.

### DESCRIPTION

**ULTRA CLEAR COMPRESSOR** oils are a universal high performance, shear stable full synthetic compressor oil based upon PAO base oil technology and advanced ashless additives.

### SUMMARY OF BENEFITS

- These advanced technology lubricants offer the ability to work across a wider temperature and pressure range as well as working for extended periods without need for oil change (up to 5,000 hours with oil analysis) due to the superior oxidation control of these lubricants.
- Superior wear protection, excellent filterability and air release make this range of lubricants a very versatile fluid for use in reciprocating, centrifugal, rotary screw, piston and sliding vane type compressors from most leading manufacturers.

#### ISO 46 -


PRODUCT CODE	PACK SIZE
30079B	IBC (1000L)
30079	205L
32079	20L

#### ISO 68 -

PRODUCT CODE	PACK SIZE
30095B	IBC (1000L)
30095	205L
32095	20L

# COMPRESSOR OILS

## VACUUM PUMP OIL VG 68 MINERAL



### DESCRIPTION

**VACUUM PUMP OIL** is a VG 68 grade lubricant designed for use in a wide variety of Vacuum pumps including dairies and the refrigeration trade.

### SUMMARY OF BENEFITS


- Blended with high quality anti-foam additives, it will resist foaming in the most arduous conditions.

### ISO 68 -

PRODUCT CODE	PACK SIZE
30090B	IBC (1000L)
30090	205L
32090	20L

# GEAR OILS

## GEAR LUBE 80W-90 & 85W-140 MINERAL



\*NOT SUITABLE FOR LIMITED SLIP DIFFERENTIALS.

### SPECIFICATIONS

SAE 80W-90, SAE 85W-140, API GL-5, GL-4, MIL-L-2105D, Borg Warner 5M-42, Mack GO-H, Rockwell, Eton, 2FTE-ML07A, 08, USS 224.

### DESCRIPTION

**GEAR LUBE 80W-90 & 85W-140** are multi-purpose, shear stable high performance gear oils based on sulfur phosphorus extreme pressure technology.

### SUMMARY OF BENEFITS

- This range will provide excellent extreme pressure protection, minimise welding, scuffing and provide superior protection in high load applications.
- Are suitable for use in gear boxes, manual transmissions, final drives, hubs and transfer cases in a wide variety of mining earthmoving, automotive, transport and agricultural applications.

#### 80W-90 -

PRODUCT CODE	PACK SIZE
30051B	IBC (1000L)
30051	205L
36051	60L
32051	20L
30451	5L
30151	1L

#### 85W-140 -

PRODUCT CODE	PACK SIZE
30052B	IBC (1000L)
30052	205L
36052	60L
32052	20L
30452	5L
30152	1L

# GEAR OILS

## LOW VIS GEAR LUBE GL-5 75W-90 MINERAL



\*NOT SUITABLE FOR LIMITED SLIP DIFFERENTIALS.

### SPECIFICATIONS

SAE 75W-90 API GL-5, GL-4, MIL-L-2105D, Borg Warner 5M-42, Ford ESP-M2C83-C, Mitsubishi ES-X-64021, 2FTE-ML08.

### DESCRIPTION

**LOW VIS 75W-90** is an extreme pressure gear lubricant formulated to provide superior extreme pressure properties ensuring smooth gear shift. Suitable for use in manual transmissions, transfer cases, steering boxes and other industrial transmission calling for a 75W-90 gear oil.

PRODUCT CODE	PACK SIZE
30050B	IBC (1000L)
30050	205L
36050	60L
32050	20L
30450	4L
30150	1L

## GEAR LUBE LS 90 MINERAL



### SPECIFICATIONS

Exceeds API GL-5, GL-4 (meets obsolete API GL-6), MIL-L-2105D, Borg Warner 5M-42, Mack GO-J, Rockwell, Eaton, Meritor 076A.

### DESCRIPTION

**GEAR LUBE LS 90** is a highly fortified extreme pressure friction modified Gear Oil specially formulated for final drives in vehicles fitted with limited slip differentials.

PRODUCT CODE	PACK SIZE
30053B	IBC (1000L)
30053	205L
36053	60L
32053	20L
30153	1L

# GEAR OILS

## ULTRA CLEAR GEAR LUBE LS 75W-85 FULL SYNTHETIC

\*SUITABLE FOR USE IN LIMITED SLIP DIFFERENTIALS.


### SPECIFICATIONS

SAE 75W-85 API GL-5, GL-4, MIL-L-2105D, Borg Warner 5M-42, Ford ESP-M2C83-C, Mitsubishi ES-X-64021.

### DESCRIPTION

**ULTRA CLEAR GEAR OIL® 75W-85** is fully synthetic friction modified, extreme pressure Gear Oils formulated with poly alpha olefin base oil technology. It will provide superior protection, thermal stability and superior EP properties to that of a mineral oil.

PRODUCT CODE	PACK SIZE
60050B	IBC (1000L)
60050	205L
66050	60L
62050	20L
60150	1L



## ULTRA CLEAR GEAR OIL® LS 75W-90 FULL SYNTHETIC

\*SUITABLE FOR USE IN LIMITED SLIP DIFFERENTIALS CALLING FOR 80W-90 OR 75W-90 VISCOSITY GRADE GEAR OIL.

### SPECIFICATIONS

SAE 75W-90, API GL-5, GL-4, MIL-L-2105D, Borg Warner 5M-42, Ford ESP-M2C83-C, Mitsubishi ES-X-64021

### DESCRIPTION

**ULTRA CLEAR GEAR OIL® LS 75W-90** is a fully synthetic extreme pressure, friction modified Gear Oil formulated with poly alpha olefin base oil technology. It will provide superior protection, thermal stability and superior EP properties to that of a mineral oil.

PRODUCT CODE	PACK SIZE
30056	205L
36056	60L
32056	20L
30456	4L



# GEAR OILS

## ULTRA CLEAR GEAR OIL® LS 80W-90 & 80W-140 FULL SYNTHETIC



\*SUITABLE FOR USE IN LIMITED SLIP DIFFERENTIALS.

### SPECIFICATIONS

SAE 80W-90, SAE 80W-140, API GL-5, GL-4, MIL-L-2105D, Borg Warner 5M-42, Mack GO-J, Rockwell, Eton.

### DESCRIPTION

**ULTRA CLEAR GEAR OIL® 80W-90 & 80W-140** are fully synthetic friction modified, extreme pressure Gear Oils formulated with poly alpha olefin base oil technology. They will provide superior protection, thermal stability and superior EP properties to that of a mineral oil. It is suitable for a wide range of manual transmission, gear boxes and final drives calling for 80W-90 and 80W-140 gear oils.

#### 80W-90 -

PRODUCT CODE	PACK SIZE
30059B	IBC (1000L)
30059	205L
36059	60L
32059	20L
30459	4L

#### 80W-140 -

PRODUCT CODE	PACK SIZE
30055B	IBC (1000L)
30055	205L
36055	60L
32055	20L
30455	4L



# GEAR OILS

## ULTRA DRIVE 90 SYNTHETIC FORTIFIED



\*SUITABLE FOR USE IN LIMITED SLIP DIFFERENTIALS.

### SPECIFICATIONS

SAE 90, SAE 90 GL-5, GL-4, ZF TE-ML 05A, 07A, 16B/C/D, 17B, 19B, MAN 342 M-2, DAF (where GL-5 axle lubricants are recommended for use), Mack GO-J, Renault (where GL-5 or MIL-PRF-2105E axle lubricants are recommended for use, MIL-PRF-2105E, Scania STO 1:0, Arvin Meritor 0-76-A/B/D, IVECO.

### DESCRIPTION

**ULTRA DRIVE 90** is a synthetic fortified ultra high performance, friction modified gear oil designed for applications operating in the most extreme conditions where high load, high temperatures and long hauls are common.

### SUMMARY OF BENEFITS

- Formulated and tested with various Road Train operators throughout Australia's Northern Territory.
- Suitable for use where both 80W-90 and 85W-140 viscosity grades are called for.
- It will provide ultimate film strength protection due to its high molecular strength and will offer excellent thermal stability.
- It will not gel when contaminated with water. Ideal for extended drain intervals.

PRODUCT CODE	PACK SIZE
30057B	IBC (1000L)
30057	205L
32057	20L

# GEAR OILS

## ULTRA SHIFT M SYNTHETIC MTF 75W FULL SYNTHETIC



### SPECIFICATIONS

SAE 75W, API GL-4, BMW MTF-LT3, Ford M2C-200-D2, MB 228.10.

### DESCRIPTION

**ULTRA SHIFT M SYNTHETIC MTF 75W** is a full synthetic high performance manual transmission fluid specifically designed to meet the requirements of modern manual transmission and dry-clutch type dual clutch transmissions. Smooth shifting, low viscosity formulation offering excellent gear and synchroniser protection for modern 6 speed manual transmissions.

PRODUCT CODE	PACK SIZE
360062	60L
320062	20L
304062	4L

## ULTRA SHIFT M SYNTHETIC MTF 75W-80 FULL SYNTHETIC



### SPECIFICATIONS

SAE 75W-80, API GL-4, Volvo 97307, ZF TE-ML-01L, 02L, 16K, MAN 341 Z-4, BMW MTF-LT-4/LT-5, Ford M2C-200-C, Honda MTF, Land Rover MTF 94, MB 231.10.

### DESCRIPTION

**ULTRA SHIFT M SYNTHETIC MTF 75W-80** is a full synthetic high performance manual transmission fluid specifically designed to meet the critical requirements of heavy duty truck and bus application in both manual and automated manual transmissions as well as meeting the needs of many passenger vehicles, utility, 4WD and vans. Smooth shifting, medium viscosity formulation offering excellent gear and synchroniser protection for modern transmissions.

PRODUCT CODE	PACK SIZE
360061	60L
320061	20L
304061	4L

# TRANSMISSION FLUIDS



## ATF DX-3 MINERAL



\*CAN BE USED IN GEAR BOXES REQUIRING ATF 85/95LE.

### SPECIFICATIONS

DX-3, Allison C4, ZF, Mercon, Sunstrand 22, Vickers 35 VQ25A, Cat TO-2.

### DESCRIPTION

**ATF DX-3** is a high quality Automatic Transmission Fluid suited to older model vehicles calling for a DX-3 or DX-2 fluid. Suited for earthmoving, construction and transport equipment calling for a DX-2 or DX-3 specification. Army designation code: OX-46.

PRODUCT CODE	PACK SIZE
30041B	IBC (1000L)
30041	205L
36041	60L
32041	20L
30441	4L
30141	1L

# TRANSMISSION FLUIDS



## SYN-TS® ATF FULL SYNTHETIC



\*NOT SUITABLE FOR CVT TRANSMISSIONS.

### SPECIFICATIONS

DX-3, DX-6, Allison: C4, TES 295, Audi, BMW, Ford: 95LE, Mercon, Mercon V, Honda ATF Z1/DW1, Hyundai SPiI/III, JASO 1a, MAN, Mazda ATF MIII/MV, MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11, Mitsubishi SPiI/III/IV/J2, Nissan 402, Matic D, J,K,S, Saab 93 165 147, Subaru ATF, ATF-HP, Suzuki 3314, 317, Toyota TIII/IV/WS, JWS3324, Voith 55.6335.XX (607,1363), Volvo 97340/41, ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C, 14B.

### DESCRIPTION

**SYN-TS® ATF** is a multi-functional fully synthetic automatic transmission fluid. It covers a wide range of applications including DX-6, DX-3, Nissan Matic, ATF 4+, Ford 95LE, Toyota and Mitsubishi. Syn-TS is ideal for extended drain intervals, heavy towing and high performance applications. Syn-TS offers unparalleled technology and performance. Suitable for use in the 6 speed ZF transmission as fitted to BF and FG falcons. Dyed red for identification.


### SUMMARY OF BENEFITS

- Formulated for transmissions working in extreme environments that are exposed to excessive temperatures, heavy loads or high performance applications.
- Will offer superior heat and frictional properties to a mineral oil while allowing for extended drain intervals.
- Meets the requirements of nearly all modern and older automatic transmissions thus is an excellent mixed fleet oil.
- SYN-TS® is the prime recommendation for Allison transmissions used in multi trailer applications.
- Meets many industry standards and OEM approvals that are not listed above, for a full listing please contact us.

PRODUCT CODE	PACK SIZE
30058B	IBC (1000L)
30058	205L
36058	60L
32058	20L
30458	4L
30158	1L

# TRANSMISSION FLUIDS

## SYN-TS® DCT FULL SYNTHETIC



### SPECIFICATIONS

Audi VW TL 052 182, VM TL 052 529, BMW 83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214 & 83 22 2 147 477, Citroen/Peugeot 9734.S2, Ford/Nissan M2C936A, Mercedes-Benz MB 236.21, Mitsubishi MZ320065 Dia-Queen SSTF-1, Porsche 999.917.080.00, Renault BOT 450, Volkswagen/Skoda/Seat VW TL 052 182, Volvo 1161838, 1161839.

### DESCRIPTION

**SYN-TS® DCT** is a full Synthetic Premium Multi-vehicle transmission fluid for use in Wet Dual Clutch Transmission (DCT/DSG) providing excellent anti-shudder protection and consistent power transmission and gear change. Suitable for use in Volkswagen Group 6 speed DSG, Ford (Getrag), Volvo, Mitsubishi, Peugeot and Citroen 6 speed dual clutch transmissions.

PRODUCT CODE	PACK SIZE
320012	20L

## SYN-TS® CVT FLUID FULL SYNTHETIC



### SPECIFICATIONS

Audi/VW (TL 52180, G 052 180, G 052 516), Dodge/Jeep (NS-2, CVTF+4), Ford (CVT30, Mercon C, CVT23), GM/Saturn (GM CVT), Honda (HMMF, HCF-2), Hyundai/Kia (SP-CVT 1), Mazda (CVTF, CVT3320), Mercedes Benz (236.20), Mini Cooper (EZL 799A), Mitsubishi (CVTF-J1, CVTF-J4), Nissan (NS-1, NS-2, NS-3), Subaru (NS-2/Lineartronic CVTF, K0425Y0710, CV-30, High Torque CVT Fluid), Suzuki (TC, NS-2, CVT Green 1, CVT Green 2), Toyota/Lexus (TC, FE).

### DESCRIPTION

**SYN-TS® CVT** is a synthetic multi-functional transmission fluid suitable for use in most Continuously Variable Transmissions including those that are chain and belt driven. Is comparable in quality to genuine CVT fluids but works across multiple vehicle makes and models making it a universal fluid.

PRODUCT CODE	PACK SIZE
60041B	IBC (1000L)
60041	205L
62041	20L
60441	4L

# TRANSMISSION FLUIDS

## SYN-TS ATF LV FULL SYNTHETIC



\*NOT SUITABLE FOR CVT TRANSMISSIONS.

### SPECIFICATIONS

DX-6, Mercon LV, Chrysler ATF +4, JASO 1-A-LV, Aisin AW-1, Honda DW-1, Nissan Matic S, Toyota WS, ZF 8 and 9 speed, GM/Ford 10 Speed automatics.

### DESCRIPTION

**SYN-TS ATF LV** is a multi-functional fully synthetic, low viscosity automatic transmission fluid. It covers a wide range of applications including DX-6, Mercon LV, ATF4+, Toyota WS, Mitsubishi Diaqueen PA, MB 236.17 and ZF 6, 8 and 9 speed transmissions. Syn-TS ATF LV is ideal for extended drain intervals, heavy towing and high performance applications. Syn-TS ATF LV offers unparalleled technology and performance.

PRODUCT CODE	PACK SIZE
300023	205L
320023	20L

# TRANSMISSION FLUIDS

## TORQUE OIL TO-4 10W, 30 & 50 MINERAL



### DESCRIPTION

The **TORQUE OIL** range is available in SAE viscosities 10W, 30 & 50. It is a multi functional heavy duty power-shift transmission fluid/drive train/clutch and hydraulic fluid suitable for use in off-highway equipment manufactured by Caterpillar, Case, Komatsu, Fiat, John Deere, Liebherr and many other global manufacturers.

It is formulated to meet Caterpillar TO-4, Allison TES 439 and C4 (obsolete), Komatsu KES 07.868.1 as well as ZF TE-ML 03C, 07D and 07F enabling the fluid to be used in mixed fleet applications. It is the ideal recommendation for use in Fuller Road Ranger and Volvo transmissions requiring a non-EP gear oil.

### 10W -

PRODUCT CODE	PACK SIZE
30047B	IBC (1000L)
30047	205L
32047	20L

### 30 -


PRODUCT CODE	PACK SIZE
30045B	IBC (1000L)
30045	205L
32045	20L

### 50 -

PRODUCT CODE	PACK SIZE
30046B	IBC (1000L)
30046	205L
32046	20L

# TRANSMISSION FLUIDS

## SYN-TORQUE TO-4 50 FULL SYNTHETIC



### DESCRIPTION

**SYN-TORQUE 50** is a fully synthetic poly alpha olefin based heavy duty transmission/drive train fluid. It is suitable for Fuller Road Ranger transmissions including those fitted with air shift systems. Designed for transmission applications both on and off-highway operating under extreme conditions including irregular servicing and high temperatures. It is suitable for extended drain intervals, usually at least double that of mineral oils.

PRODUCT CODE	PACK SIZE
30054B	IBC (1000L)
30054	205L
32054	20L



# TRANSMISSION FLUIDS

## AGRIBLUE UTTF 10W-30 SYNTHETIC



\*FORMULATED WITH VAPOUR PHASE INHIBITOR.

### SPECIFICATIONS

John Deere: JDM J20A, J20B, J20C, J20D, J14B, J14C, JD21A, JDT303, Quatrol, New Holland: ESN-M2C134-D, FNHA-2-C-200.00, FNHA-2-C-201.00 Case International: MS 1206, 1204, 1207, 1210, JIC 145, 143, 144, 185, International Harvester B5-B6, White Q1826,1705,1802, 1826, 1766, 1722, 1766B, Type 55, AGCO 821XL, Steiger, Versatile, Deutz-Allis, Fiat, Kubota UDT, Massey Ferguson: M-1110, 1127A/B, 1129A, 1135, 1141, 1143, 1145, ZF: TE-ML 03E, 03F, 05F, 06K, Cat TO-2, Allis-Chalmers Power Fluid 821, Deutz-Allis: 272843, 257541, 246634, Allison: C2, C3, C4.

### DESCRIPTION

**AGRIBLUE UTTF 10W-30** is a synthetic fortified ultra high performance Universal Tractor Transmission Fluid (UTTF) formulated with a Vapour Phase Inhibitor (VPI).

### SUMMARY OF BENEFITS

- VPI's slowly release an anti-corrosive film protecting gear teeth and engine parts exposed to the atmosphere during long idle periods.
- Designed for use in transmissions, final drives, hydraulics, wet clutches and wet brakes of modern tractors including those calling for a common oil and is recommended for use in 10W-20 or 20W-30 applications.
- Significantly increased gear wear protection.
- Proven field performance and good anti-foam characteristics.
- Excellent shear stability performance is maintained and very high thermal/oxidation stability provide long fluid life.
- Good water tolerance ensures hydraulic performance is maintained.
- Low Copper activity and good filterability.

PRODUCT CODE	PACK SIZE
30048B	IBC (1000L)
30048	205L
32048	20L

# TRANSMISSION FLUIDS

## AGRITRANS MINERAL



### SPECIFICATIONS

API GL-4, SAE 80, John Deere: JDM J20A, J20B, J20C, J20D, J14B, J14C, JD21A, JDT303, Quatrol, New Holland: ESN-M2C134-D, FNHA-2-C-200.00, FNHA-2-C-201.00 Case International: MS 1206, 1204, 1207, 1210, JIC 145, 143, 144, 185, International Harvester B5-B6, White Q1826,1705,1802, 1826, 1766, 1722, 1766B, Type 55, AGCO 821XL, Steiger, Versatile, Deutz-Allis, Fiat, Kubota UDT, Massey Ferguson: M-1110, 1127A/B, 1129A, 1135, 1141, 1143, 1145, ZF: TEMPL 03E, 03F, 05F, 06K, Cat TO-2, Allis-Chalmers Power Fluid 821, Deutz-Allis: 272843, 257541, 246634, Allison: C2, C3, C4.

### DESCRIPTION

**AGRITRANS** is a high quality, premium grade OEM approved Universal Tractor Transmission Fluid (UTTF) meeting the requirement of modern and older tractor manufacturers.


### SUMMARY OF BENEFITS

- This product has millions of hours in field testing in the demanding Australian environment.
- It is a high zinc formulation designed for use in transmissions, final drives, hydraulics, wet clutches and wet brakes of modern tractors including those calling for common oil and is recommended for use in 10W-30 or 20W-30 applications.
- Meets many industry standards and OEM approvals that are not listed above. For a full listing - please contact us.

PRODUCT CODE	PACK SIZE
30044B	IBC (1000L)
30044	205L
36044	60L
32044	20L
30544	5L

# INDUSTRIAL PRODUCTS

## INDUSTRIAL GEAR OIL RANGE MINERAL



### SPECIFICATIONS

ISO 100, 150, 220, 320, 460, 680 & 800 , General EP. AGMA, 9005-ED2. DIN 51 517 Part 3. David Brown, S1.53.101(E) Table E. USS 224, ISO 12925-1 CKC/CKD, FIVES CINCINNATI MACHINE GEAR.

### DESCRIPTION

**INDUSTRIAL GEAR OIL** is available in viscosity grades ISO 68, 100, 150, 220, 320, 460, 680 & 800. It is extreme pressure, high load carrying gear oil formulated with Sulfur Phosphorus additive technology. It is suitable for a wide range of Industrial, Agricultural and Commercial applications calling for an EP Gear Oil.

#### ISO 100 -

PRODUCT CODE	PACK SIZE
60000B	IBC (1000L)
60000	205L
62000	20L

#### ISO 150 -


PRODUCT CODE	PACK SIZE
30066B	IBC (1000L)
30066	205L
32066	20L

#### ISO 220 -

PRODUCT CODE	PACK SIZE
30067B	IBC (1000L)
30067	205L
32067	20L

# INDUSTRIAL PRODUCTS

## INDUSTRIAL GEAR OIL RANGE MINERAL



CONTINUED..

### ISO 320 -

PRODUCT CODE	PACK SIZE
30068B	IBC (1000L)
30068	205L
32068	20L

### ISO 460 -

PRODUCT CODE	PACK SIZE
30069B	IBC (1000L)
30069	205L
32069	20L

### ISO 680 -

PRODUCT CODE	PACK SIZE
30077B	IBC (1000L)
30077	205L
32077	20L

### ISO 800 -

PRODUCT CODE	PACK SIZE
30035	205L

# INDUSTRIAL PRODUCTS

## SYN-GEAR INDUSTRIAL GEAR OIL RANGE FULL SYNTHETIC



### SPECIFICATIONS

ISO 32, 100, 150, 220, 320, 460, General EP. AGMA, 9005-E02. DIN 51 517 Part 3. David Brown, S1.53.101(E) Table E. USS 224, ISO 12925-1 CKC/CKD, FIVES CINCINNATI MACHINE GEAR.

### DESCRIPTION

**SYN-GEAR INDUSTRIAL GEAR OIL** is a full synthetic, PAO based industrial gear oil. It is formulated with high performance base oil and additive packages and is a lead free formulation.

#### ISO 32 -

PRODUCT CODE	PACK SIZE
300051	205L

#### ISO 100 -

PRODUCT CODE	PACK SIZE
30038B	IBC (1000L)
32038	20L

#### ISO 150 -


PRODUCT CODE	PACK SIZE
30039B	IBC (1000L)
30039	205L
32039	20L

#### ISO 220 -

PRODUCT CODE	PACK SIZE
30089B	IBC (1000L)
30089	205L
32089	20L

# INDUSTRIAL PRODUCTS

## SYN-GEAR INDUSTRIAL GEAR OIL RANGE FULL SYNTHETIC



CONTINUED..

### ISO 320 -

PRODUCT CODE	PACK SIZE
30003B	IBC (1000L)
30003	205L
32003	20L

### ISO 460 -

PRODUCT CODE	PACK SIZE
30031B	IBC (1000L)
30031	205L
32031	20L

# INDUSTRIAL PRODUCTS

## SOLCUT EP MINERAL




### DESCRIPTION

**SOLCUT EP** is a general purpose water soluble cutting fluid designed for a wide variety of applications such as milling and turning.

PRODUCT CODE	PACK SIZE
30088B	IBC (1000L)
30088	205L
32088	20L

## TACWAY 68 MINERAL



### SPECIFICATIONS

ISO 68. General EP. DIN 51524 Part II, US Steel 224.

### DESCRIPTION

**TACWAY 68** is a General Purpose Slideway machine oil. They are formulated with anti-wear additives and tackifiers to reduce sling off. Suitable for use in slideways, lathes, machine tools and other types of equipment calling for a tacky, non-corrosive lubricant.

### ISO 68 -

PRODUCT CODE	PACK SIZE
30073B	IBC (1000L)
30073	205L
32073	20L

# GREASES

## RED LITH TAK GREASE EXTREME PRESSURE



### DESCRIPTION

**RED LITH TAK GREASE** is a metal soap based NLGI 2 high performance grease formulated with an extra tacky additive package, reducing sling off and water washout.

PRODUCT CODE	PACK SIZE
40050	180KG
42050	20KG
40450	450GM

## SUPER BLUE GREASE METAL COMPLEX



### DESCRIPTION

**SUPER BLUE GREASE** is a metal complex grease suitable for all types of wheel bearings including slow and high speed, high temperature applications (including disc brakes), high load and those operating in extreme environments.

PRODUCT CODE	PACK SIZE
40051	180KG
45551	55KG
42051	20KG
42562	2.5KG
40451	450GM
44451	400GM



# GREASES

## BLACK TAK MOLYPLEX GREASE METAL COMPLEX EXTREME PRESSURE



### DESCRIPTION

**BLACK TAK** is a severe duty 5% molybdenum disulfide metal complex mine and quarry grease. Specifically formulated for a wide range of quarry and mining equipment operating under heavy loads in the most difficult environments. The extreme pressure and anti-wear properties enable the grease to give long service life and outstanding boundary lubrication under high load and shock loading conditions from low temperature to very high temperature environments.

PRODUCT CODE	PACK SIZE
40052	180KG
45552	55KG
42052	20KG
40452	450GM
44452	400GM

## TRUCK AND FARM GREASE METAL COMPLEX



### DESCRIPTION

**TRUCK AND FARM GREASE** is an ultra tacky, heavy duty extremely high quality metal complex grease suitable for a wide range of applications for transport, earthmoving and farming applications. Suitable for general greasing, bearings, hammers and shock load applications.

PRODUCT CODE	PACK SIZE
60054	180KG
62054	20KG
60454	450GM



## MARINE & PREMIUM WHEEL BEARING METAL COMPLEX EXTREME PRESSURE

### DESCRIPTION

**MARINE AND PREMIUM WHEEL BEARING GREASE** is a high performance metal complex grease specifically formulated for the harsh marine environment. A highly water resistant grease with a special mixed metal complex soap and selected corrosion inhibitors protects the lubricated components against corrosion even in salt water environments.

The very high load carrying capability, high temperature performance, low oil bleed and enhanced corrosion protection characteristics of the grease make it an excellent choice for all wheel bearing applications including those on boat trailers which are repeatedly immersed in salt water.

PRODUCT CODE	PACK SIZE
40041	180KG
42041	20KG
40541	500GM
40441	450GM



## RED RUBBER GREASE INORGANIC THICKENER

### DESCRIPTION

**RED RUBBER GREASE** is an inorganically thickened, bio-degradable grease for use on rubber components used in hydraulic and braking systems where compatibility with natural, SBR, NBR and other rubber tubes, hoses or seals is required. Due to the vegetable oil base contained within the lubricant, it is highly resistant to attack by hydrocarbon solvents including petrol and diesel.

PRODUCT CODE	PACK SIZE
40539	500GM



## COPPER ANTI-SEIZE INORGANIC THICKENER

### DESCRIPTION

**COPPER ANTI-SEIZE** is a lead free compound for threaded connection of pipes, flanges and threaded fasteners subject to high temperatures and/or corrosive environments. The product overcomes galling on assembly and greatly reduces the effort in dismantling previously assembled equipment.

As an anti-seize agent the product is suitable for use at elevated temperatures, up to 1,100°C. COPPER ANTI-SEIZE also protects against seizure in pipe fittings and valves in highly corrosive environments and those subject to chemical attack such as found in petrochemical plants, gas refining and oil exploration.

PRODUCT CODE	PACK SIZE
40540	500GM



## EASY FLOW GREASE LITHIUM EXTREME PRESSURE

### DESCRIPTION

**EASY FLOW GREASE** is a range of semi fluid extreme pressure grease available in the below grades. Recommended for systems calling for a fluid or semi fluid grease and are recommended for use in most auto greasing systems in earthmoving, road transport and construction.

#### NLGI-00 -

PRODUCT CODE	PACK SIZE
42063	20KG
40463	450GM

#### NLGI-1 -

PRODUCT CODE	PACK SIZE
42064	20KG

#### NLGI-0 -

PRODUCT CODE	PACK SIZE
42065	20KG

# GREASES

## GREASE GUN



### DESCRIPTION

**HD PISTOL GRIP GREASE GUN** with aluminium pump head that provides grease pressure up to 8000PSI. Suitable for our 450gram grease cartridges.

PRODUCT CODE	PACK SIZE
20124	SUITS 450GM CARTRIDGES

# COOLANTS

## ALL FLEET HDD COOLANT PRE-MIXED & CONCENTRATE



### DESCRIPTION

**ALL FLEET HDD COOLANT** is a high quality long life heavy duty diesel engine coolant based on hybrid technology which offers conventional technology coupled with Organic Acid Technology (OAT). It is a 3 in 1, offering anti-freeze (-37c), anti-rust and anti-boil. Suitable for use in most cooling systems including those containing aluminium. It has a service life of six years, 12,000 hours or 1,000,000km - whichever comes first. For brand requirements, please contact us.

### PRE-MIXED -

PRODUCT CODE	PACK SIZE
40055B	IBC (1000L)
40055	205L
42055	20L
40555	5L

### CONCENTRATE -

PRODUCT CODE	PACK SIZE
40054B	IBC (1000L)
40054	205L
42054	20L
40554	5L

# COOLANTS

## LONG LIFE COOLANT RED ORGANIC PRE-MIXED & CONCENTRATED



### DESCRIPTION

**LONG LIFE COOLANT RED** is a premium quality, organic, long life anti-boil/anti-freeze coolant pre-mix and concentrate, based on carboxylate technology and contains no silicates, borates, phosphates, nitrites, nitrates or amines. Suitable for both automotive and heavy duty diesel engines. It is available in both concentrate and pre-mixed.

### PRE-MIXED -

PRODUCT CODE	PACK SIZE
40046B	IBC (1000L)
40046	205L
42046	20L

### CONCENTRATE -

PRODUCT CODE	PACK SIZE
40056B	IBC (1000L)
40056	205L
42056	20L
40556	5L

# AEROSOLS



## FULL RANGE OF AEROSOLS FOR ALL YOUR AUTOMOTIVE NEEDS

**HEAVY DUTY DEGREASER** is a powerful multi-purpose degreaser designed to remove grease and grime from numerous surfaces.

PRODUCT CODE	PACK SIZE
64099	400GM
68099	840ML



**CARBY AND THROTTLE BODY CLEANER** rapidly removes carbon deposits, oil, sludge, gum and varnish from interior or carburetor and throttle body, shaft and plate.

PRODUCT CODE	PACK SIZE
64095	400GM
68095	840ML



**MULTI PURPOSE DWF SPRAY** is a heavy duty water dispersant designed to displace moisture and lubricate, protect and start wet motors.

PRODUCT CODE	PACK SIZE
64096	400GM



**BRAKE CLEANER** is a dynamic non chlorinated, non toxic cleaner designed to rapidly remove brake fluids, oils, dust, dirt, grease and other contaminants from brake linings, disc pads, drums, clutch plates, rotors, cylinders and springs. Also available in a 20L drum - #42213.

PRODUCT CODE	PACK SIZE
64098	350GM
68098	840ML



**TYRE SHINE** gives your tyres, louvres, bumpers, mud flaps and side mouldings a 'new' appearance and aids in the prevention of dirt forming on your tyres. Also available in a 20L drum - #62097.

PRODUCT CODE	PACK SIZE
64097	350GM



# WORKSHOP MAINTENANCE

## ORGANIC SPILL FIX OIL ABSORBENT KIT



### DESCRIPTION

**SPILL FIX OIL ABSORBENT** is made from organic products and can be used on all petroleum products and coolant. Easy to spread and can absorb up to ten times its own weight. This absorbment is biodegradable and meets EPA standards.

#### SPILLFIX EMERGENCY KIT -

PRODUCT CODE	PACK SIZE
40010	N/A

#### SPILLFIX FLOOR SWEEP -

PRODUCT CODE	PACK SIZE
40012	50L
40011	15L

## PREMIUM FLOOR SWEEP



### DESCRIPTION

**PREMIUM FLOOR SWEEP** is a powerful absorbent for clean up of liquids on all surfaces. Leaves no residue. Low dust formula which will reduce clean up time. Made from recycled, treated organic by-products.

PRODUCT CODE	PACK SIZE
42020	20L



# WORKSHOP MAINTENANCE

## AIR TOOL OIL ISO 32



### DESCRIPTION

**AIR TOOL OIL ISO 32** is a mineral based lubricant designed for lubricating the internal parts of pneumatic air tools.

PRODUCT CODE	PACK SIZE
30193	1L
30192	250ML

## HYDRAULIC JACK OIL ISO 32



### DESCRIPTION

**HYDRAULIC JACK OIL ISO 32** is a mineral based oil suitable for use in hydraulic trolley and bottle type jacks as well as electric car hoists.

PRODUCT CODE	PACK SIZE
30194	1L

## DRUM PUMP

### DESCRIPTION

**205/60L DRUM PUMP** Aluminium lever pump to suit 205L/60L oil drums.


**20L DRUM PUMP** With a 1.5 metre dispensing hose suitable for most 20lt oil containers.

PRODUCT CODE	PACK SIZE
20084	SUITABLE FOR 205L/60L DRUMS
20086	SUITABLE FOR 20L DRUMS



# WORKSHOP MAINTENANCE

## DOT 3 & DOT 4 BRAKE FLUID



### DESCRIPTION

**DOT 3 & 4 BRAKE FLUID** are high performance, high temperature moisture resistant brake and clutch fluids suitable for use in modern hydraulic systems.

#### DOT 3 -

PRODUCT CODE	PACK SIZE
42015	20L

#### DOT 4 -

PRODUCT CODE	PACK SIZE
42001	20L
40501	5L
40101	500ML

## SOLVENT BASED DEGREASER



### DESCRIPTION

**SOLVENT BASED DEGREASER** is a powerful, water soluble solvent based degreaser that will remove grease, oil, grime, dirt and scum. It is suitable for cleaning engines, parts and all other types of off road equipment.

PRODUCT CODE	PACK SIZE
40008	200L
42008	20L

# WORKSHOP MAINTENANCE

## WATER BASED DEGREASER



### DESCRIPTION

**WATER BASED DEGREASER** is a heavy duty, powerful cleaner specially designed for industrial and home applications. Easily removes oil and grease. Suitable for cleaning of driveways, vehicles, trailers, tools and garden equipment.

PRODUCT CODE	PACK SIZE
40018	200L
42018	20L

## SUPER BLUE TRUCK WASH



### DESCRIPTION

**SUPER BLUE TRUCK WASH** is a water based wash containing no caustic and is PH neutral hence it is friendly to paint and will not dull aluminium or plastic. It is a biodegradable, quick break concentrated solution suitable for cars, trucks, boats and off road equipment.

PRODUCT CODE	PACK SIZE
40007B	IBC (1000L)
40007	205L
42007	20L

## BAGS OF RAGS




### DESCRIPTION

**BAGS OF RAGS** are assorted mixed cotton rags perfect for workshops and general use.

PRODUCT CODE	PACK SIZE
192	20KG
40016	5KG

# WORKSHOP MAINTENANCE

## GREEN KLEEN HAND CLEANER



### DESCRIPTION

**GREEN KLEEN HAND CLEANER** is a high quality petroleum based hand cleaner. Removes dirt, grease, ink, oil and general grime from the skin.

PRODUCT CODE	PACK SIZE
42019	20L



## CITRA GRIT HAND CLEANER

### DESCRIPTION

**CITRA GRIT HAND CLEANER** is a heavy duty, water based, citrus hand cleaner made from organic ingredients that removes grease, oil, dirt and grime.

PRODUCT CODE	PACK SIZE
620230	20L
605230	5L

## FLEET TEST SAMPLE KITS



### DESCRIPTION

**FLEET TEST KITS** are an early warning system developed to diagnose problems before they lead to failure. These kits can be used for all types of systems including engines, gear boxes, hydraulics, differentials in mechanical, mining, earthmoving, agriculture, transport, generators, marine and manufacturing.

PRODUCT CODE	PACK SIZE
990	1 SAMPLE KIT
988	BOX OF 10 KITS

# SPECIALISED PRODUCTS

## CLEARONOX (ADBLUE)



### DESCRIPTION

**CLEARONOX** is a 32.5% solution of high purity urea in demineralised water, also known as AdBlue. It reduces exhaust emission levels of nitrogen oxide products (NOx) from diesel engines.

It is Australian manufactured and meets or exceeds the ISO 22241 international standard.

Gulf Western Diesel Clearonox can be used in all SCR engines.

- 205L AdBlue Rotary hand pump is now in stock under product code: 20171.

PRODUCT CODE	PACK SIZE
40078B	IBC (1000L)
40078	210L
42078	20L

## SUPERTAK CHAIN BAR OIL ISO 150



### SPECIFICATIONS

ISO 150, EP.

### DESCRIPTION

**SUPERTAK CHAIN BAR OIL** is an extremely tacky, viscous chain saw/bar lubricant formulated from high quality base oils to provide superior chain and bar protection, condition seals and reduce sling off. Popular amongst logging contractors and professionals due to its strong EP performance and extra tacky formulation.

PRODUCT CODE	PACK SIZE
30080B	IBC (1000L)
30080	205L
32080	20L
30480	4L
30180	1L

# SPECIALISED PRODUCTS

## LOCO OIL 9



### SPECIFICATIONS

LMOA Generation VI (compatible with LMOA Generation V and GE GEN 4LL), SAE 40.

### DESCRIPTION

**LOCO OIL 9** is a non-chlorinated, zinc free and low ash heavy duty diesel engine oil suitable for late model GE and EMD engines used in locomotive and stationary engine applications operating on low/ultra low sulfur fuels.

PRODUCT CODE	PACK SIZE
60056B	IBC (1000L)
60056	205L

## JOURNAL BEARING OIL HEAVY DUTY



### SPECIFICATIONS

ISO 150, EP.

### DESCRIPTION

**JOURNAL BEARING OIL** is a premium quality, high viscosity, rust inhibited railroad journal bearing oil. Due to its high viscosity and extreme pressure additives the product assists in reducing friction in heavily loaded bearings.

PRODUCT CODE	PACK SIZE
300357	205L
320357	20L

# SPECIALISED PRODUCTS

## POWER STEERING FLUID



### DESCRIPTION

**POWER STEERING FLUID** is a high quality oil manufactured for use in power steering systems of modern vehicles calling for DX-3, DX-2 type fluid. Dyed Red.

PRODUCT CODE	PACK SIZE
30111	1L

## ROCK DRILL 100, 150 & 320



### SPECIFICATIONS

ISO 100, 150 & 320. General EP.

### DESCRIPTION

**ROCK DRILL 100, 150 & 320** is specialised pneumatic air tool oil suitable for jack hammers, rock drills, centralised lubricators and rammers. It is formulated with anti-corrosive additives, tackifiers, EP additives and an oil soluble molybdenum compound offering excellent lubrication properties in the most extreme environments.

#### ISO 100 -

PRODUCT CODE	PACK SIZE
60049B	IBC (1000L)

#### ISO 150 -

PRODUCT CODE	PACK SIZE
30049	205L
32049	20L

#### ISO 320 -

PRODUCT CODE	PACK SIZE
30096	205L
32096	20L



# GULF WESTERN OIL

## GO THE DISTANCE



**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUSTRALIA) PTY LTD**  
**WEBSITE: WWW.GULFWESTERN.COM.AU - TOLL FREE NUMBER: 1800 248 919**

**NSW HEAD OFFICE:** 92 Links Road, St Marys, NSW 2760  
Phone Number: 02 9673 9600 - Fax Number: 02 9673 9696

**NEWCASTLE WAREHOUSE:** 5/77 Stenhouse Drive, Cameron Park, NSW 2285  
Phone Number: 0404 481 384

**QLD WAREHOUSE:** 6 Commerce Court, Clontarf, QLD 4019  
Phone Number: 07 3283 7239 - Fax Number: 07 3284 1813

**VICTORIA WAREHOUSE:** Unit 6, 31-35 Burgess Road, Bayswater North, VIC 3153  
Phone Number: 0438 732 356

**SHEPPARTON WAREHOUSE:** 68 Mitchell Street, Shepparton, VIC 3630  
Phone Number: 03 5831 3121 - Fax Number: 03 5821 3899

**SOUTH AUSTRALIA:** 21 Aruma Street, Regency Park SA 5010 Australia  
Phone: 0498 341 423 - Sales: 0487 376 168

**Version 14. 2023 | Part Number: #50155**

